

LATEX - ADHESIVES

Product	Polymer Type	Typical properties			Recommended Applications	Description
		Solids %	pH	Viscosity Cps		
R160M	Vinyl- acetate	44-46	3.5-4.5	6000-10000	Paper packaging, Book binding, Wood working & General purpose pasting.	Quick tack, Fast setting & excellent heat resistance.
SL5112A	Vinyl- acrylic	44-46	4.0-5.0	8000-12000	Paper packaging, Book binding, paper tube winding Wood working & General purpose pasting.	Quick tack, Fast setting & excellent heat resistance.
R160S	Vinyl- acetate	48-50	3.5-4.5	6000-10000	Paper packaging, Book binding, Wood working & General purpose pasting.	Quick tack, Fast setting & excellent heat resistance. Resistance to Acids Alkalies & Oil.
SL160L	Vinyl- acetate	39.5-40.5	4.0-5.0	1500-2500	Paper packaging, Book binding, Wood working & General purpose pasting.	Quick tack, Fast setting & good flow properties.
A2017L	Vinyl- acetate	28-29	3.5-4.5	24000-30000	Paper packaging, Book binding, Wood working & General purpose pasting	Quick tack, Fast setting & good flow properties.
A2017R	Vinyl- acetate	33-35	3.5-4.5	48000-68000	Paper packaging, Book binding, Wood working & General purpose pasting.	Quick tack, Fast setting & good flow properties.
A4020D	Vinyl- acetate	22.5-23.5	3.5-4.5	1500-3500	Paper packaging, Carton Pasting & General purpose pasting	Quickly drying in to a clear tack free film. More Economical.
SL1265A	Vinyl- acetate	12-14	4-5	1500-2500	Paper packaging, Carton Pasting & General purpose pasting	Quickly drying in to a clear tack free film. More Economical.

LATEX – ADHESIVES Continued

UCAR Latex	Polymer Type	Typical properties			Recommended Applications	Description
		Solids %	pH	Viscosity cps		
S937A	Vinyl / Acrylic	49-51	4-5	3000-6000	Paper to Paper, Aluminium to Paper, PP/PVC/PU to Paper Lamination.	Co-polymer ,widely use for OPP Film lamination to paper/boards
SL977A	Vinyl / Acrylic	49-51	4.5-5.5	2000- 4000	PP Film, Aluminium film, PVC film lamination on boards/paper	Co-polymer, specially designed for OPP lamination.
S165H	Vinyl / Acrylic	49-51	4-5	15000-20000	Difficult surface adhesives and Table adhesive for textiles	Designed for hand pasting applications.